FXONE

Coding and Marking Made Easy

Print directly onto cartons, trays and sacks to eliminate the need for costly pre-printed packaging or expensive labels

High Resolution

1 to 8 lines of print, with

1-25.4 mm print height.

Simple Screen &

For local control of printer

speed and direction and message delay.

True Type Font &

Enables message creation

in any font and in any

Ink Saver Mode

Reduce ink consumption by

2 Years Warranty* Extended warranty available

*Terms and conditions apply

Keyboard

Unicode

language.

up to 75%.

TT

Coding & Marking



Pc Connectivity Via USB cable, RS485 or Ethernet for direct message creation or factory network system.

Out of the Box Installation

With minimal components for maximum reliability.



Touch Controller Simple interactive windows programming with FX App. Reliable printing in one click.



Large Oil Based Ink Cartridge

Low cost coding and clean inking system, ideal for printing on to porous

surfaces.



ASY CODING

Graphics, Logos & Barcodes

Easily import JPEG, PNG & BMP graphics using the FX App.



1D & 2D Barcodes High resolution printing of 1D and 2D barcodes (QR Codes - data matrix) to include variable data.



Networking

Manage multiple printer from one place. Monitor progress, track fault and gain insights with print analytics.



Multi Port Connection

For encoders, external alarms and alternative product detection devices.



Software for all your case coding application



Simple interactive windows programming

Multi language support



Full Integration with our DLL

Available on PC & 7" Touch screen controller

Networking & print analytics

Advanced printer management

FXOŃE

Features

- Prints in any orientation
- 1 to 8 lines of print
- 1mm- 25.4mm total print heigh
- High resolution
- Prints text, graphics, logos and barcodes
- Prints time and multiple date formats
- Continuous repeat print capability
- 240m/min print speed (1200m/min for barcode and 2mm text) HIGH SPEED
- Single start/stop print button
- Visual alarm indicator including ink low
- Message width, delay and print direction control
- Product detection photocell
- Weight 1.7 Kg (excluding ink catridge and brackets)
- Size 242 x 178 x 90mm

Connectivity

- RS232 and RS485 for Foenix Touch controller
- USB-A memory stick included
- USB-B for cable connection
- Ethernet (optional)
- Prints text, graphics, logos and barcodes
- I/O port for encoder, alarm beacon and external photocells

Ink

- Sealed replaceable ink cartridge (up to 15 million characters)
- Oil based inks for porous surfaces
- Mineral Oil Free ink available
- UV inks for instant LED curing
- Various colours

Electrical

• 90-260 VAC to 24VDC power supply included

FX APP

Features

- Compatible with Windows XP and above
- Intuitive icon led message creation
- True Type Font and Unicode supported
- Graphics, logos & barcodes directly imported in JPEG and BMP format
- Time and multiple date formats
- Ink saver print mode
- Unlimited message storage
- Multi language support

FX ONE TOUCH CONTROLLER

Features

- 7" Touch Screen
- Simple interactive windows programming
- Uses FX App

Connectivity

- USB-A, USB-B, RS232, RS485 Multi port, Ethernet (Optional)
- 24 v DC input
- Support external alarms, beacons, encoders
- Auto programming with barcode reader

www.easycoding.com

EASY CODING

Poeta Joan Maragall, 70 28020 MADRID · SPAIN Telf.: +34 919 21 35 75 easycoding@easycoding.es





